

OFFICE OF NAVAL RESEARCH

Contract N00014-86-K-0043

TECHNICAL REPORT No. 96

Light Scattering from an Atom Near the Surface of a Superlattice

by

Xiao-shen Li, D. L. Lin and Thomas F. George

Prepared for Publication

in

Atomic and Molecular Physics

Edited by M. S. Z. Chagtai

Aligarh Muslim University, Aligarh, India

Departments of Chemistry and Physics
State University of New York at Buffalo
Buffalo, New York 14260

April 1989

Reproduction in whole or in part is permitted for any purpose of the United States Government.

This document has been approved for public release and sale; its distribution is unlimited.

DTIC
ELECTE
APR 11 1989
S D

AD-A206 670

89 4 10 016

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE

REPORT DOCUMENTATION PAGE				Form Approved OMB No. 0704-0188	
1a. REPORT SECURITY CLASSIFICATION Unclassified			1b. RESTRICTIVE MARKINGS		
2a. SECURITY CLASSIFICATION AUTHORITY			3. DISTRIBUTION/AVAILABILITY OF REPORT Approved for public release; distribution unlimited		
2b. DECLASSIFICATION/DOWNGRADING SCHEDULE					
4. PERFORMING ORGANIZATION REPORT NUMBER(S) UBUFFALO/DC/89/TR-96			5. MONITORING ORGANIZATION REPORT NUMBER(S)		
6a. NAME OF PERFORMING ORGANIZATION Depts. Chemistry & Physics State University of New York		6b. OFFICE SYMBOL (If applicable)	7a. NAME OF MONITORING ORGANIZATION		
6c. ADDRESS (City, State, and ZIP Code) Fronczak Hall, Amherst Campus Buffalo, New York 14260			7b. ADDRESS (City, State, and ZIP Code) Chemistry Program 800 N. Quincy Street Arlington, Virginia 22217		
8a. NAME OF FUNDING/SPONSORING ORGANIZATION Office of Naval Research		8b. OFFICE SYMBOL (If applicable)	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER Contract N00014-86-K-0043		
8c. ADDRESS (City, State, and ZIP Code) Chemistry Program 800 N. Quincy Street Arlington, Virginia 22217			10. SOURCE OF FUNDING NUMBERS		
			PROGRAM ELEMENT NO.	PROJECT NO.	TASK NO.
					WORK UNIT ACCESSION NO.
11. TITLE (Include Security Classification) Light Scattering from an Atom Near the Surface of a Superlattice					
12. PERSONAL AUTHOR(S) Xiao-shen Li, D. L. Lin and Thomas F. George					
13a. TYPE OF REPORT		13b. TIME COVERED FROM _____ TO _____		14. DATE OF REPORT (Year, Month, Day)	
				15. PAGE COUNT	
16. SUPPLEMENTARY NOTATION Prepared for publication in Atomic and Molecular Physics, Edited by M. S. Z. Chagtai, Aligarh Muslim Univeristy, Aligarh, India					
17. COSATI CODES			18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)		
FIELD	GROUP	SUB-GROUP	ATOM, LIGHT SCATTERING,		
			NEAR, SUPERLATTICE, RESONANCE FLUORESCENCE		
			METAL-INSULATOR SEMICLASSICAL THEORY.		
19. ABSTRACT (Continue on reverse if necessary and identify by block number) A semiclassical theory is developed to treat the interaction of radiation with an atom located near the surface of an m-component superlattice. For the special case of $m = 2$, the radiation penetration depth into the superlattice and the resonance fluorescence spectrum are calculated numerically for superlattices of metal-insulator construction. The results show sensitive dependence on the plasma frequency in the metal layer as well as on the dielectric function and width of the insulator layer.					
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT <input checked="" type="checkbox"/> UNCLASSIFIED/UNLIMITED <input checked="" type="checkbox"/> SAME AS RPT. <input type="checkbox"/> DTIC USERS			21. ABSTRACT SECURITY CLASSIFICATION Unclassified		
22a. NAME OF RESPONSIBLE INDIVIDUAL Dr. David L. Nelson			22b. TELEPHONE (Include Area Code) (202) 696-4410		22c. OFFICE SYMBOL

Light scattering from an atom near the surface of a superlattice

Xiao-shen Li*, D. L. Lin and Thomas F. George
Departments of Chemistry and Physics & Astronomy
239 Fronczak Hall
State University of New York at Buffalo
Buffalo, New York 14260

Abstract

A semiclassical theory is developed to treat the interaction of radiation with an atom located near the surface of an m -component superlattice. For the special case of $m = 2$, the radiation penetration depth into the superlattice and the resonance fluorescence spectrum are calculated numerically for superlattices of metal-insulator construction. The results show sensitive dependence on the plasma frequency in the metal layer as well as on the dielectric function and width of the insulator layer.

* On leave of absence from the Shanghai Institute of Metallurgy, Chinese Academy of Sciences, Shanghai, P. R. China

Accession For	
NTIS CRA&I	<input checked="checked" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

I. Introduction

When an atom or molecule near or adsorbed on a solid surface interacts with a radiation field, the presence of the surface and substrate greatly influences the optical phenomena. Examples include surface-enhanced Raman scattering,^{1,2} coherence and energy transfer in spontaneous emission,³⁻⁶ surface-induced resonance fluorescence,⁷⁻¹³ and so on. The optical properties of adspecies on a solid surface may provide a sensitive probe of electronic and other structure of the substrate, and hence has prompted a careful re-examination of the optics of surfaces. Once the mechanism of these optical processes is fully understood and brought under experimental control, it should become a powerful tool for the analysis of surface processes.

On the other hand, when a strong driving coherent field is nearly on resonance with the atomic transition frequency, the field places the driven atom in an environment in which the probability of stimulated emission may exceed that of spontaneous emission. When this is the case, as Stark splitting of the atomic levels, Rabi oscillations of the level occupation probabilities and nutational oscillations of the stimulated field intensity are enhanced. Consequently, resonance fluorescence⁷⁻¹⁴ and other nonlinear optical phenomena become possible.^{15,16} Because multiphoton transitions are just as important as the single-photon transition in such light-driving processes, the ordinary perturbation method is no longer reliable.

In the surface-free case such as atoms in a gas,¹⁵ such processes can be effectively dealt with by the well-known optical Bloch equation (OBE). With the presence of the surface, a set of surface-dressed optical Bloch equations (SBE) has been derived⁷⁻¹⁰ to treat such problems as the effects of surface-reflected photons, the resonance interaction of an atom with surface plasmons, collisional dephasing of the atom due to the gas atoms in the

medium, and random phase fluctuation of the intense laser field. Resonance fluorescence has been investigated for an adatom near a flat metallic surface^{7,8} and near a rough metallic surface represented by a hemispheroid protrusion on a flat surface.^{9,10} More recently, a different approach involving reservoir theory¹⁷ and Dekkars's quantization procedure for a dissipative system^{18,19} has been adopted to derive another set of the SBE.¹¹ The resonance fluorescence spectrum of an adatom has been analyzed for the following cases: an adatom is considered near the surface of a metal sphere with the size of the sphere taken into account,¹² and the problem is considered again near the surface of a semi-infinite conductor and dielectric superlattice in which the frequency of the transverse optical phonon matches that of the adatomic transition.¹¹

We investigate, in this paper, the resonance fluorescence spectrum of an adatom near the surface of a superlattice. The adatom is taken as an emitting dipole. The emitted field is reflected back from the surface and interfaces and is coupled to the radiating dipole whose dynamical behavior is therefore totally changed. We first develop the theory for a general superlattice composed of m different layers per period. This theory may be applied to simulate quasi-periodic systems.^{20,21} Numerical results are given for the special case of $m = 2$.

II. Theory

For a two-level atom driven by a monochromatic laser field with

$$E(t) = \frac{1}{2} (E e^{i\omega_0 t} + E^* e^{-i\omega_0 t}) , \quad (1)$$

the SBE are given by¹²⁻¹⁴

$$\frac{d}{dt} \begin{bmatrix} \langle S^+ \rangle \\ \langle S^z \rangle \\ \langle S^- \rangle \end{bmatrix} = \begin{bmatrix} i(\Delta + \Omega^S) - \gamma & i\Omega & 0 \\ i\Omega^*/2 & -2\gamma & -i\Omega/2 \\ 0 & -i\Omega^* & -i(\Delta + \Omega^S) - \gamma \end{bmatrix} \begin{bmatrix} \langle S^+ \rangle \\ \langle S^z \rangle \\ \langle S^- \rangle \end{bmatrix} - \begin{bmatrix} 0 \\ \gamma \\ 0 \end{bmatrix} \quad (2)$$

The notation is as follows. The adatom with a transition frequency ω is located at a distance d_0 away from the surface of the superlattice. The matrix element of the electric dipole moment operator is denoted by $|p|$, and E and ω_0 are the amplitude and frequency of the external laser field, respectively. The detuning is $\Delta = \omega - \omega_0$, and the Rabi frequency is $\Omega = |p|E$. The transition probability amplitude is proportional to the projection operators defined by

$$S^+ = |+\times-|$$

$$S^z = \frac{1}{2} (|+\times+| - |-\times-|) \quad (3)$$

$$S^- = |-\times+|$$

The total decay rate of the adatom can be written as

$$\gamma = \gamma^0 + \gamma^S, \quad (4)$$

where γ^0 is the decay rate in the absence of the substrate,²²

$$\gamma^0 = \frac{2}{3} \sqrt{\epsilon_0} |p|^2 \omega^3 / c^3, \quad (4a)$$

and

$$\gamma^S = |p|^2 \operatorname{Im} f(d_0) \quad (4b)$$

is the decay rate induced by the surface. The frequency shift of the spontaneous radiation due to the surface is

$$\Omega^S = |p|^2 \operatorname{Re} f(d_0) \quad , \quad (5)$$

and the function $f(d_0)$ is determined by^{11, 13, 14}

$$E_R = |p| f(d_0) S^- = p f(d_0) \quad , \quad (6)$$

where E_R is the component of the reflected field \vec{E}_R in the direction of \vec{p} .

Equation (2) agrees with the result from linear response theory⁶ when the adatom is taken as a harmonic oscillator. With the aid of the regression theorem for correlation functions,^{23, 24} we find from the SBE the well-known results of the incoherent resonance fluorescence spectrum,¹²⁻¹⁴

$$\phi_{\text{inc}}(\nu) = \frac{1}{2} |\Omega|^4 \gamma (D^2 + \frac{1}{2} |\Omega|^2 + 4\gamma^2) / (\frac{1}{2} |\Omega|^2 + |z|^2) (x^2 + y^2) \quad , \quad (7)$$

where $D = \nu - \omega_0$, $z = \gamma + i(\Delta + \Omega^S)$, $x = 2\gamma(\frac{1}{2}|\Omega|^2 + |z|^2 - 2D^2)$, and $y = D(|\Omega|^2 + |z|^2 + 4\gamma^2 - D^2)$.

Consider now a semi-infinite superlattice consisting of m different layers per period as shown in Fig. 1. The surface is taken to be the xy -plane, and an adatom with dipole moment \vec{p} is located at $\vec{r} = \vec{r}_0 = (0, 0, -d_0)$. The dielectric constants and thicknesses of these layers are ϵ_i and d_i ,

respectively, where $i = 1, 2, \dots, m$. The reflected electric field at r_0 from a substrate of a two-component superlattice has been worked out in Ref. 8. We now generalize the theory to the case of an m -component superlattice in which the thickness of each period is L . The set of equations for the fields \vec{E} and \vec{H} in different materials can be obtained directly from Maxwell's equations. The results are^{6,11,13,14}

$$\nabla^2 \vec{E} + \epsilon_0 k_0^2 \vec{E} = -4\pi [k_0^2 \vec{P} + \frac{1}{\epsilon_0} \nabla(\nabla \cdot \vec{P})]$$

$$\vec{H} = \frac{1}{ik_0} \nabla \times \vec{E}, \quad z < 0 \quad (8a)$$

$$\nabla^2 \vec{E}_1 + \epsilon_1 k_0^2 \vec{E}_1 = 0, \quad \nabla \cdot \vec{E}_1 = 0$$

$$\vec{H}_1 = \frac{1}{ik_0} \nabla \times \vec{E}_1, \quad nL \leq z \leq nL + d_1 \quad (8b)$$

$$\nabla^2 \vec{E}_2 + \epsilon_2 k_0^2 \vec{E}_2 = 0, \quad \nabla \cdot \vec{E}_2 = 0$$

$$\vec{H}_2 = \frac{1}{ik_1} \nabla \times \vec{E}_2, \quad nL + d_1 \leq z \leq nL + d_1 + d_2 \quad (8c)$$

$$\nabla^2 \vec{E}_m + \epsilon_m k_0^2 \vec{E}_m = 0, \quad \nabla \cdot \vec{E}_m = 0$$

$$\vec{H}_m = \frac{1}{ik_0} \nabla \times \vec{E}_m, \quad (n+1)L - d_m \leq z \leq (n+1)L, \quad (8d)$$

where $k_0 = \omega/c$ is the wave number in vacuum, n labels the period in the superlattice, and \vec{P} is defined by

$$\vec{P}(\vec{r}, \omega) = \vec{p}(\omega) \delta(\vec{r} - \vec{r}_0) \quad (9)$$

The solution for the electric field in Eq. (8a) can be written as

$$\vec{E}(\vec{r}, \omega) = \int du \int dv \vec{\mathcal{E}}(u, v, \omega) e^{i\vec{k}' \cdot \vec{r}} + \vec{E}_p(\vec{r}, \omega), \quad z < 0 \quad (10)$$

$$\vec{k}' \cdot \vec{\mathcal{E}} = 0, \quad \vec{k}' = (k_{\parallel}, -w), \quad w^2 = \epsilon_0 k_0^2 - k_{\parallel}^2, \quad \text{Im } w \geq 0$$

where we have defined $\vec{k} = (\vec{k}_{\parallel}, w) = (u, v, w)$. The field due to the dipole is

$$\begin{aligned} \vec{E}_p(\vec{r}, \omega) = & -\frac{1}{2\pi i} \int du \int dv \frac{k_0^2 \vec{p} - \epsilon_0^{-1} \nabla(\vec{p} \cdot \nabla)}{w} \\ & \times \exp[iu(x-x_0) + iv(y-y_0) + iw|z-z_0|] \quad (11) \end{aligned}$$

Because of the periodic structure of semi-infinite superlattice, the electric field may have a Bloch-wave-like form with an envelope function decaying exponentially with increasing z . Thus we find solutions for the electric field of Eqs. (8b)-(8d)^{13,25} as

$$\begin{aligned} \vec{E}_1(\vec{r}, \omega) = & \int du \int dv \left\{ \vec{\mathcal{E}}_1^{(+)}(u, v, \omega) e^{iw_1(z-nL)} \right. \\ & \left. + \vec{\mathcal{E}}_1^{(-)}(u, v, \omega) e^{-iw_1(z-nL)} \right\} e^{i\vec{k}_{\parallel} \cdot \vec{r} - \beta nL} \\ \vec{k}_1 \cdot \vec{\mathcal{E}}_1^{(+)} = & \vec{k}'_1 \cdot \vec{\mathcal{E}}_1^{(-)} = 0 \quad (12a) \end{aligned}$$

$$\vec{k}_1 = (\vec{k}_{\parallel}, w_1) \quad , \quad \vec{k}'_1 = (\vec{k}_{\parallel}, -w_1)$$

$$w_1^2 = \epsilon_1 k_o^2 - k_{\parallel}^2 \quad , \quad nL \leq z \leq nL + d_1$$

$$\vec{E}_2(\vec{r}, \omega) = \int du \int dv \left\{ \vec{\mathcal{E}}_2^{(+)}(u, v, \omega) e^{i w_2(z - nL - d_1)} \right. \\ \left. + \vec{\mathcal{E}}_2^{(-)}(u, v, \omega) e^{-i w_2(z - nL - d_1)} \right\} e^{i \vec{k}_{\parallel} \cdot \vec{r} - \beta nL}$$

$$\vec{k}_2 \cdot \vec{\mathcal{E}}_2^{(+)} = \vec{k}_2 \cdot \vec{\mathcal{E}}_2^{(-)} = 0$$

$$\vec{k}_2 = (\vec{k}_{\parallel}, w_2) \quad , \quad \vec{k}'_2 = (\vec{k}_{\parallel}, -w_2)$$

$$w_2^2 = \epsilon_2 k_o^2 - k_{\parallel}^2 \quad , \quad nL + d_1 \leq z \leq nL + d_1 + d_2$$

$$\vec{E}_m(\vec{r}, \omega) = \int du \int dv \left\{ \vec{\mathcal{E}}_m^{(+)}(u, v, \omega) e^{i w_m[z - (n+1)L + d_m]} \right. \\ \left. + \vec{\mathcal{E}}_m^{(-)}(u, v, \omega) e^{-i w_m[z - (n+1)L + d_m]} \right\} e^{i \vec{k}_{\parallel} \cdot \vec{r} - \beta nL}$$

$$\vec{k}_m \cdot \vec{\mathcal{E}}_m^{(+)} = \vec{k}_m \cdot \vec{\mathcal{E}}_m^{(-)} = 0$$

$$\vec{k}_m = (\vec{k}_{\parallel}, w_m) \quad , \quad \vec{k}'_m = (\vec{k}_{\parallel}, -w_m)$$

$$w_m^2 = \epsilon_m k_o^2 - k_{\parallel}^2 \quad , \quad (n+1)L - d_m \leq z \leq (n+1)L$$

(12b)

(12c)

where we have introduced a parameter β to measure the rate of absorption.

For simplicity, we assume that the dipole is orientated perpendicular to the interfaces of the superlattice. We can then follow the standard procedure to find the component of the reflected field along the dipole direction at \vec{r}_0 . Equations (12) together with the usual Maxwell boundary conditions at the surface and interfaces then yield

$$E_R = \frac{i}{\epsilon_0} k_0^3 p \phi(d_0) \quad (13)$$

$$\phi(d_0) = \int_0^\infty \frac{k^3 dk}{U_0} e^{2iU_0 \hat{d}_0} \psi_1 / \psi_2 \quad (14a)$$

$$\begin{aligned} \psi_1 = & -2^{m-1} (1 - V_{10}) e^{\beta L} \\ & + \sum_{N_m=0}^1 \left\{ [1 - (-1)^{N_m} V_{m0}] \sum_{N_2, \dots, N_{m-1}=0}^1 \left\{ \exp\left[i \sum_{j=1}^m (-1)^{N_j} U_j \hat{d}_j\right] \right. \right. \\ & \times \left. \prod_{\ell=1}^{m-1} [1 + (-1)^{N_\ell + N_{\ell+1}} V_{\ell, \ell+1}] \right\} \Big\} \end{aligned} \quad (14b)$$

$$\begin{aligned} \psi_2 = & 2^{m-1} (1 + V_{10}) e^{\beta L} \\ & - \sum_{N_m=0}^1 \left\{ [1 + (-1)^{N_m} V_{m0}] \sum_{N_2, \dots, N_{m-1}=0}^1 \left\{ \exp\left[i \sum_{j=1}^m (-1)^{N_j} U_j \hat{d}_j\right] \right. \right. \\ & \times \left. \prod_{\ell=1}^{m-1} [1 + (-1)^{N_\ell + N_{\ell+1}} V_{\ell, \ell+1}] \right\} \Big\} , \end{aligned} \quad (14c)$$

where $N_1 = N_{m+1} = 0$, $V_{n\ell} = \epsilon_n U_\ell / \epsilon_\ell U_n$, $U_\ell = \sqrt{\epsilon_\ell} k$, $\hat{d}_\ell = k_0 d_\ell$, and

$n = 1, 2, \dots, m$. Because of the periodicity of the superlattice, we define $v_{n,m+1} = v_{m,1}$. The symbol \sum' means summation when $m \geq 3$ and no summation when $m = 2$. The attenuation factor $e^{\beta L}$ is determined by the equations

$$e^{\beta L} = \frac{1}{2} [\eta \pm \sqrt{\eta^2 - 4}] \quad , \quad \text{Re} \beta \geq 0 \quad (15)$$

$$\eta = 2^{1-m} \sum_{N_2 \dots N_m=0}^1 \left\{ \cos \left[\sum_{j=1}^m (-1)^{N_j} U_j \hat{d}_j \right] \prod_{\ell=1}^m [1 + (-1)^{N_\ell + N_{\ell+1}} v_{\ell, \ell+1}] \right\} \quad (16)$$

If the superlattice is composed of highly-dissipative materials, the incident electric field cannot go very deep into the layers. When the condition $L \ll \lambda$ is satisfied, which is usually the case, we can define the penetration depth for the field as

$$\hat{d}_p = \alpha L = (\text{Re} \beta)^{-1} \quad , \quad (17)$$

where α is a positive number.

It is observed from the above equations that both the reflected field and the penetration depth depend strongly upon the number of layers per period as well as the thickness and dielectric properties of the individual layer. Meanwhile, the surface plasmon TM modes are determined by the zeroes of the denominator, namely, $\psi_2 = 0$. The properties of the surface plasmon as well as the interference between the electric fields reflected and refracted at each interface play very important roles in the determination of E_R , both its amplitude and its phase.

To find the spontaneous decay rate and frequency shift, we first note that a comparison of (6) and (13) yields $f(d_o) = \frac{i}{\epsilon_o} k_o^3 \phi(d_o)$. Substituting into (4) and (5), we obtain

$$\gamma = 1 + \frac{3}{2} \epsilon_o^{-3/2} \text{Re } \phi(d_o) \quad (18a)$$

$$\Omega^s = - \frac{3}{2} \epsilon_o^{-3/2} \text{Im } \phi(d_o) \quad (18b)$$

expressed in the unit of γ^o .

III. Numerical results

The theory developed above is valid for any number of layers in one period of the superlattice. In what follows, we shall apply it to a typical case of two-component superlattices. The first layer in each period is a metal with dielectric function $\epsilon_1(\omega) = 1 - \omega_p^2/(\omega^2 + i\omega\gamma_p)$, while the other is an insulator with a wide energy gap. Setting $m = 2$ in Eqs. (14b), (14c) and (16), we have

$$\begin{aligned} \psi_1 = & -2(1-v_{10}) e^{\beta L} + [(1-v_{20})(1+v_{12}) e^{iU_2 \hat{d}_2} \\ & + (1+v_{20})(1-v_{12}) e^{-iU_2 \hat{d}_2}] e^{iU_1 \hat{d}_1} \end{aligned} \quad (19a)$$

$$\psi_2 = 2(1+v_{10}) e^{\beta L} - [(1+v_{20})(1+v_{12}) e^{iU_2 \hat{d}_2}$$

$$+ (1-v_{20})(1-v_{12})e^{-iU_2\hat{d}_2} e^{iU_1\hat{d}_1} \quad (19b)$$

$$\eta = \frac{1}{2} \left[(1+v_{12})(1+v_{21})\cos(U_1\hat{d}_1 + U_2\hat{d}_2) + (1-v_{12})(1-v_{21})\cos(U_1\hat{d}_1 - U_2\hat{d}_2) \right] \quad (20)$$

We look at the penetration depth for normal incidence of light with frequency ω . From (15), (17) and (20), we calculate \hat{d}_p as a function of the atomic transition frequency. The results for different layer thicknesses are shown in Fig. 2, in which we have defined $x = \omega/\omega_p$. It is observed that for fixed ω , the penetration depth has a sensitive dependence on the charge carrier density in the metal layers. It decreases with increasing carrier density, which is easy to understand because a large carrier density results in more collisions and therefore more energy loss of the incident radiation. Furthermore, we also see that the larger the fraction that the nonabsorptive insulator in each period occupies, the deeper the field penetrates into the superlattice.

The incoherent part of the resonance fluorescence spectrum may be investigated numerically. We find again that the spectrum is extremely sensitive to the plasma frequency or the density of charge carriers in the metallic layers. When ω is fixed, different carrier densities may result in spectra with different number and shape (height and width) of peaks as well as the position of sidebands. The situation is illustrated in Fig. 3 in which the spectrum is shown as a function of D [defined just beneath Eq. (7)] for various values of x . That the sidebands do not appear in the case of the one-peak spectrum may be understood as follows.

When x is such that ψ_2 is near its minimum, the resonance condition for the surface plasmon to exist is nearly satisfied. The creation of the surface plasmon then enhances the absorption and results in a single-peak spectrum. This is because non-radiative energy transfer to the surface plasmon becomes very strong near resonance and hence greatly increases the absorption of the incident energy by the surface via the adatom. Consequently, the scattered field intensity is too weak to produce the sidebands of the spectrum. On the other hand, when x is such that ψ_2 is far from its minimum, this absorption process is insignificant, and the spectrum has three peaks which are all high and narrow, provided that there is no significant absorption resulting from the multibeam interference.

Acknowledgments

This research was partially supported by the Office of Naval Research, the National Science Foundation under Grant CHE-8620274, and the Air Force Office of Scientific Research (AFSC), United States Air Force, under Contract F49620-86-C-0009. The United States Government is authorized to copy and distribute reprints for governmental purposes notwithstanding any copyright notation hereon.

References

1. G. C. Schatz, Surface-Enhanced Raman Scattering (Plenum, New York, 1983), p. 35.
2. P. Das and H. Metiu, J. Phys. Chem. 89, 4681 (1985).
3. R. R. Chance, A. Prock and R. Silbey, Adv. Chem. Phys. 37, 1 (1978).
4. H. Kuhn, J. Chem. Phys. 53, 101 (1970).
5. K. H. Drexhage, J. Lumin. 1-2, 693 (1970); Progress in Optics, Vol. XII (North-Holland, Amsterdam, 1974), 165.
6. G. S. Agarwal, Phys. Rev. Lett. 32, 703 (1974); Phys. Rev. A 11, 230 (1975); 11, 243 (1975); 11 253 (1975); 12, 1475 (1975); Opt. Commun. 42, 205 (1982).
7. X. Y. Huang, J. T. Lin and T. F. George, J. Chem. Phys. 80, 893 (1984).
8. X. Y. Huang and T. F. George, J. Phys. Chem. 88, 4801 (1984).
9. X. Y. Huang, K. T. Lee and T. F. George, J. Chem. Phys. 85, 567 (1986).
10. J. T. Lin, X. Y. Huang and T. F. George, J. Opt. Soc. Am. B 4, 219 (1987).
11. X. S. Li and C. D. Gong, Phys Rev. A 35, 1595 (1987).
12. X. S. Li and C. D. Gong, J. Phys. B 21, 1429 (1988).
13. X. S. Li and C. D. Gong, Phys. Rev. B, in press.
14. X. S. Li and C. D. Gong, Phys. Lett. A 131, 138 (1988).
15. L. Allen and J. H. Eberly, Optical Resonance and Two-Level Atoms (Wiley, New York, 1975).
16. J. H. Eberly, "Quantum Optics with Very Intense Lasers," a lecture presented at the Workshop on Lasers and Laser Spectroscopy, Kanpur, 1987 (unpublished).
17. M. Sargent, M. O. Scully and W. E. Lamb, Laser Physics (Addison-Wesley, Reading, Mass., 1974), Chap. 17.
18. H. Dekker, Physica, A 95, 311 (1979).
19. L. S. Zhang, Physica A 117, 355 (1983).
20. See B. Simon, Adv. Appl. Math. 3, 463 (1982), and references therein.
21. J. P. Lu, Odagaki and J. L. Birman, Phys. Rev. B 33, 4809 (1986).
22. G. S. Agarwal and S. V. O'Neil, Phys. Rev. B 28, 487 (1983).

23. M. Lax, Phys. Rev. 157, 213 (1967).
24. B. R. Mollow, Phys. Rev. 188, 1969 (1969); Phys. Rev. A 15, 1023 (1977).
25. R. E. Camley and D. L. Mills, Phys. Rev. B 29, 1695 (1984).

Figure Captions

1. Schematic diagram of a semi-infinite superlattice with period L . An atomic dipole moment is located in front of the surface.
2. Penetration depth as a function of x for a metal-insulator two-component superlattice. The parameters employed are: $\gamma_p = 0.01 \omega_p$, $\epsilon_2 = 0.3$, $d_1 = 0.1$ and (a) $d_1 = 0.5$, (b) $d_2 = 0.2$.
3. Incoherent resonance fluorescence spectrum from a two-component metal-insulator superlattice for different x values. The parameters are: $\Delta = 2.0$, $|\Omega| = 45$, $\gamma_p = 0.01 \omega_p$, $\epsilon_2 = 3.0$, $d_2 = 0.1$, $d_3 = 0.5$ and (a) $x = 0.1$, (b) $x = 0.2$, (c) $x = 0.3$, (d) $x = 0.4$.

Fig. 1




Fig. 2





Fig. 3



TECHNICAL REPORT DISTRIBUTION LIST, GEN

	<u>No. Copies</u>		<u>No. Copies</u>
Office of Naval Research Attn: Code 1113 800 N. Quincy Street Arlington, Virginia 22217-5000	2	Dr. David Young Code 334 NORDA NSTL, Mississippi 39529	1
Dr. Bernard Douda Naval Weapons Support Center Code 50C Crane, Indiana 47522-5050	1	Naval Weapons Center Attn: Dr. Ron Atkins Chemistry Division China Lake, California 93555	1
Naval Civil Engineering Laboratory Attn: Dr. R. W. Drisko, Code L52 Port Hueneme, California 93401	1	Scientific Advisor Commandant of the Marine Corps Code RD-1 Washington, D.C. 20380	1
Defense Technical Information Center Building 5, Cameron Station Alexandria, Virginia 22314	12 high quality	U.S. Army Research Office Attn: CRD-AA-IP P.O. Box 12211 Research Triangle Park, NC 27709	1
DTNSRDC Attn: Dr. H. Singerman Applied Chemistry Division Annapolis, Maryland 21401	1	Mr. John Boyle Materials Branch Naval Ship Engineering Center Philadelphia, Pennsylvania 19112	1
Dr. William Tolles Superintendent Chemistry Division, Code 6100 Naval Research Laboratory Washington, D.C. 20375-5000	1	Naval Ocean Systems Center Attn: Dr. S. Yamamoto Marine Sciences Division San Diego, California 91232	1
		Dr. David L. Nelson Chemistry Division Office of Naval Research 800 North Quincy Street Arlington, Virginia 22217	1

ABSTRACTS DISTRIBUTION LIST, 056/625/629

Dr. J. E. Jensen
Hughes Research Laboratory
3011 Malibu Canyon Road
Malibu, California 90265

Dr. C. B. Harris
Department of Chemistry
University of California
Berkeley, California 94720

Dr. J. H. Weaver
Department of Chemical Engineering
and Materials Science
University of Minnesota
Minneapolis, Minnesota 55455

Dr. F. Kutzler
Department of Chemistry
Box 5055
Tennessee Technological University
Cookeville, Tennessee 38501

Dr. A. Reisman
Microelectronics Center of North Carolina
Research Triangle Park, North Carolina
27709

Dr. D. DiLella
Chemistry Department
George Washington University
Washington D.C. 20052

Dr. M. Grunze
Laboratory for Surface Science and
Technology
University of Maine
Orono, Maine 04469

Dr. R. Reeves
Chemistry Department
Rensselaer Polytechnic Institute
Troy, New York 12181

Dr. J. Butler
Naval Research Laboratory
Code 6115
Washington D.C. 20375-5000

Dr. Steven M. George
Stanford University
Department of Chemistry
Stanford, CA 94305

Dr. L. Interante
Chemistry Department
Rensselaer Polytechnic Institute
Troy, New York 12181

Dr. Mark Johnson
Yale University
Department of Chemistry
New Haven, CT 06511-8118

Dr. Irvin Heard
Chemistry and Physics Department
Lincoln University
Lincoln University, Pennsylvania 19352

Dr. W. Knauer
Hughes Research Laboratory
3011 Malibu Canyon Road
Malibu, California 90265

Dr. K.J. Klaubunde
Department of Chemistry
Kansas State University
Manhattan, Kansas 66506

ABSTRACTS DISTRIBUTION LIST, 056/625/629

Dr. G. A. Somorjai
Department of Chemistry
University of California
Berkeley, California 94720

Dr. J. Murday
Naval Research Laboratory
Code 6170
Washington, D.C. 20375-5000

Dr. J. B. Hudson
Materials Division
Rensselaer Polytechnic Institute
Troy, New York 12181

Dr. Theodore E. Madey
Surface Chemistry Section
Department of Commerce
National Bureau of Standards
Washington, D.C. 20234

Dr. J. E. Demuth
IBM Corporation
Thomas J. Watson Research Center
P.O. Box 218
Yorktown Heights, New York 10598

Dr. M. G. Lagally
Department of Metallurgical
and Mining Engineering
University of Wisconsin
Madison, Wisconsin 53706

Dr. R. P. Van Duyne
Chemistry Department
Northwestern University
Evanston, Illinois 60637

Dr. J. M. White
Department of Chemistry
University of Texas
Austin, Texas 78712

Dr. D. E. Harrison
Department of Physics
Naval Postgraduate School
Monterey, California 93940

Dr. R. L. Park
Director, Center of Materials
Research
University of Maryland
College Park, Maryland 20742

Dr. W. T. Peria
Electrical Engineering Department
University of Minnesota
Minneapolis, Minnesota 55455

Dr. Keith H. Johnson
Department of Metallurgy and
Materials Science
Massachusetts Institute of Technology
Cambridge, Massachusetts 02139

Dr. S. Sibener
Department of Chemistry
James Franck Institute
5640 Ellis Avenue
Chicago, Illinois 60637

Dr. Arnold Green
Quantum Surface Dynamics Branch
Code 3817
Naval Weapons Center
China Lake, California 93555

Dr. A. Wold
Department of Chemistry
Brown University
Providence, Rhode Island 02912

Dr. S. L. Bernasek
Department of Chemistry
Princeton University
Princeton, New Jersey 08544

Dr. W. Kohn
Department of Physics
University of California, San Diego
La Jolla, California 92037

ABSTRACTS DISTRIBUTION LIST, 056/625/629

Dr. F. Carter
Code 6170
Naval Research Laboratory
Washington, D.C. 20375-5000

Dr. Richard Colton
Code 6170
Naval Research Laboratory
Washington, D.C. 20375-5000

Dr. Dan Pierce
National Bureau of Standards
Optical Physics Division
Washington, D.C. 20234

Dr. R. Stanley Williams
Department of Chemistry
University of California
Los Angeles, California 90024

Dr. R. P. Messmer
Materials Characterization Lab.
General Electric Company
Schenectady, New York 22217

Dr. Robert Gomer
Department of Chemistry
James Franck Institute
5640 Ellis Avenue
Chicago, Illinois 60637

Dr. Ronald Lee
R301
Naval Surface Weapons Center
White Oak
Silver Spring, Maryland 20910

Dr. Paul Schoen
Code 6190
Naval Research Laboratory
Washington, D.C. 20375-5000

Dr. John T. Yates
Department of Chemistry
University of Pittsburgh
Pittsburgh, Pennsylvania 15260

Dr. Richard Greene
Code 5230
Naval Research Laboratory
Washington, D.C. 20375-5000

Dr. L. Kesmodel
Department of Physics
Indiana University
Bloomington, Indiana 47403

Dr. K. C. Janda
University of Pittsburgh
Chemistry Building
Pittsburg, PA 15260

Dr. E. A. Irene
Department of Chemistry
University of North Carolina
Chapel Hill, North Carolina 27514

Dr. Adam Heller
Bell Laboratories
Murray Hill, New Jersey 07974

Dr. Martin Fleischmann
Department of Chemistry
University of Southampton
Southampton SO9 5NH
UNITED KINGDOM

Dr. H. Tachikawa
Chemistry Department
Jackson State University
Jackson, Mississippi 39217

Dr. John W. Wilkins
Cornell University
Laboratory of Atomic and
Solid State Physics
Ithaca, New York 14853

ABSTRACTS DISTRIBUTION LIST, 056/625/629

Dr. R. G. Wallis
Department of Physics
University of California
Irvine, California 92664

Dr. D. Ramaker
Chemistry Department
George Washington University
Washington, D.C. 20052

Dr. J. C. Hemminger
Chemistry Department
University of California
Irvine, California 92717

Dr. T. F. George
Chemistry Department
University of Rochester
Rochester, New York 14627

Dr. G. Rubloff
IBM
Thomas J. Watson Research Center
P.O. Box 218
Yorktown Heights, New York 10598

Dr. Horia Metiu
Chemistry Department
University of California
Santa Barbara, California 93106

Dr. W. Goddard
Department of Chemistry and Chemical
Engineering
California Institute of Technology
Pasadena, California 91125

Dr. P. Hansma
Department of Physics
University of California
Santa Barbara, California 93106

Dr. J. Baldeschwieler
Department of Chemistry and
Chemical Engineering
California Institute of Technology
Pasadena, California 91125

Dr. J. T. Keiser
Department of Chemistry
University of Richmond
Richmond, Virginia 23173

Dr. R. W. Plummer
Department of Physics
University of Pennsylvania
Philadelphia, Pennsylvania 19104

Dr. E. Yeager
Department of Chemistry
Case Western Reserve University
Cleveland, Ohio 44106

Dr. N. Winograd
Department of Chemistry
Pennsylvania State University
University Park, Pennsylvania 16802

Dr. Roald Hoffmann
Department of Chemistry
Cornell University
Ithaca, New York 14853

Dr. A. Steckl
Department of Electrical and
Systems Engineering
Rensselaer Polytechnic Institute
Troy, New York 12181

Dr. G.H. Morrison
Department of Chemistry
Cornell University
Ithaca, New York 14853